



FEATURES

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

BENEFITS

- Lift up to 90m
- Flow rate up to 28,800 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

Bore part number: 4C5122200-B40
Dam Floating part number: 4C5122200-D40



4C5122200

TDH	L/MIN	L/DAY
10	80	28,800
20	75	27,000
30	70	25,200
40	63	22,680
50	57	20,520
60	50	18,000
70	40	14,400
80	32	11,520
90	26	9,360

SOLAR PUMP SYSTEM INCLUDES:



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



8x370w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

ACCESSORIES

6101 - Tank switch 6045NO - Pressure switch 6112 - 1.5" Double acting float valve 6015 - Sacrificial anode 1¼"



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$300+GST



Double acting float valve For use with Pressure Switch - \$300+GST



Anode \$120+GST



Shipping Dimensions
1x Crate 440 x 60 x 65cm @ 280kg
1x Pallet 200 x 115 x 45cm @ 190kg