



FEATURES

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

BENEFITS

- Lift up to 90m
- Flow rate up to 13,680 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

Bore part number: 4HRH800-B40 Dam Floating part number: 4HRH800-D40 Nationwide Delivery part number: XFREX2



SOLAR PUMP SYSTEM INCLUDES:



4HRSS-H Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



3x370w Mono Crystalline Solar Panels



Bore Cap or Dam Float



4HRH800 L/MIN

38

37

36

34

33

30

28

26

15

TDH

20 30

40

50

60

70

80

90

L/DAY

13,680

13,320

12,960

12,240

11,880 10.800

10,080

9,360 5,400

Low water protection (bore kit only)

ACCESSORIES

6101 - Tank switch 6045NO - Pressure switch 6112 - 1.5" Double acting float valve 6014 - 4" HR sacrificial anode



Tank full switch inc 20m cable \$165+GST



Heavy Duty

Cyclone Rated Pole

Mount Frame

Pressure Switch 12 bar inc gauge & fittings \$300+GST



Double acting float valve For use with Pressure Switch - \$300+GST





Shipping Dimensions \$120+GST 1x Crate 210 x 100 x 55cm @ 195kg